

230 Series

		Designation		Dimensions in mm					Basic Load Ratings(KN)			Speed(U/min)		Fatigue limit load (kN)		
select	Inquiry	cylindrical	conical	d	D	B	b	rs	min	Weight(kg)	Dynamic(Cr)	Static(Cor)	Reference speed	Limiting speed		
23022	23022K	110	170	45	5.5	2	3.71	282	455	3400	4300	46.5				
23024	23024K	120	180	46	5.5	2	4.05	296	495	3200	4000	53				
23026	23026K	130	200	52	8.3	2	5.9	375	620	2800	3600	62				
23028	23028K	140	210	53	8.3	2	6.35	405	690	2800	3600	62				
23030	23030K	150	225	56	8.3	2.1	7.73	445	775	2400	3200	73.5				
23032	23032K	160	240	60	11.1	2.1	9.42	505	885	2400	3000	83				
23034	23034K	170	260	67	11.1	2.1	12.7	630	1080	2200	2800	100				
23036	23036K	180	280	74	13.9	2.1	16.7	740	1290	2000	2600	114				
23038	23038K	190	290	75	13.9	2.1	17.7	755	1350	1900	2400	122				
23040	23040K	200	310	82	13.9	2.1	22.7	915	1620	1800	2200	137				
23044	23044K	220	340	90	13.9	3	29.9	1060	1920	1600	2000	163				
23048	23048K	240	360	92	13.9	3	33.4	1130	2140	1500	1900	176				
23052	23052K	260	400	104	16.7	4	48.5	1420	2620	1300	1700	212				
23056	23056K	280	420	106	16.7	4	52.4	1510	2920	1300	1600	224				
23064	23064K	320	480	121	16.7	4	78	2240	3800	1100	1400	285				
23068	23068K	340	520	133	22.3	5	105	2700	4550	1000	1300	335				
23072	23072K	360	540	134	22.3	5	110	2750	4800	950	1200	345				
23076	23076K	380	560	135	22.3	5	150	2900	5000	900	1200	360				
23080	23080K	400	600	148	22.3	5	150	3250	5700	850	1100	400				
23084	23084K	420	620	150	22.3	5	155	3400	6000	600	1100	415				
23088	23088K	440	650	157	22.3	6	180	3650	6550	560	1000	450				
23092	23092K	460	680	163	22.3	6	180	3650	6550	560	1000	450				
23096	23096K	480	700	165	22.3	6	205	3900	6950	560	950	465				
230/500	230/500K	500	720	167	22.3	6	225	4150	7800	500	900	510				
230/530	230/530K	530	780	185	22.3	6	310	5100	9300	450	800	630				
230/560	230/560K	560	820	195	22.3	6	355	5600	10200	430	750	680				
230/600	230/600K	600	870	200	22.3	6	405	6000	11400	400	700	750				
230/630	230/630K	630	920	212	22.3	7.5	485	6700	12500	380	670	800				
230/670	230/670K	670	980	230	22.3	7.5	600	7650	14600	340	600	915				
230/710	230/710K	710	1030	236	22.3	7.5	670	8300	16300	320	560	1000				