

239 Series

select	Inquiry Designation		Principal Dimensions(mm)					Weight (kg)	Basic Load Ratings(KN)		Limited Speed(rpm)	PU
			d	D	B	b	rs min		Dynamic(Cr)	Static(Cor)	Grease	Oil kN
23936	180	250	52	5,5	2	7,90	431	830	2400	2800	76,5	
23936K	180	250	52	2	440	835	1200	1800	7.95	2800	76.5	
23936KW33C3	180	250	52	2	440	835	1200	1800	7.95	2800	76.5	
23936W33C3	180	250	52	2	440	835	1200	1800	8.21	2800	76.5	
23938	190	260	52	5,5	2	8,30	414	800	2200	2600	76,5	
23938K	190	260	52	2	460	890	1100	1700	8.34	2600	76.5	
23938KW33C3	190	260	52	2	460	890	1100	1700	8.34	2600	76.5	
23938W33C3	190	260	52	2	460	890	1100	1700	8.6	2600	76.5	
23940	200	280	60	8,3	2,1	11,5	546	1040	2000	2400	93	
23940K	200	280	60	2.1	545	1100	1000	1600	11.7	2400	93	
23940KW33C3	200	280	60	2.1	545	1100	1000	1600	11.7	2400	93	
23940W33C3	200	280	60	2.1	545	1100	1000	1600	12.1	2400	93	
23944	220	300	60	8,3	2,1	12,5	546	1080	1900	2200	93	
23944K	220	300	60	2.1	565	1170	930	1400	12.7	2200	93	
23944KW33C3	220	300	60	2.1	565	1170	930	1400	12.7	2200	93	
23944W33C3	220	300	60	2.1	565	1170	930	1400	13.1	2200	93	
23948	240	320	60	8,3	2,1	13,5	564	1160	1700	2000	98	
23948K	240	320	60	2.1	565	1190	840	1300	13.6	2000	98	
23948KW33C3	240	320	60	2.1	565	1190	840	1300	13.6	2000	98	
23948W33C3	240	320	60	2.1	565	1190	840	1300	14	2000	98	
23952	260	360	75	8,3	2,1	23,5	880	1800	1500	1900	156	
23952K	260	360	75	2.1	760	1580	770	1200	23.3	1900	156	
23952KW33C3	260	360	75	2.1	760	1580	770	1200	23.3	1900	156	
23952W33C3	260	360	75	2.1	760	1580	770	1200	24	1900	156	
23956	280	380	75	11,1	2,1	25,0	845	1760	1400	1700	143	
23956K	280	380	75	2.1	830	1750	710	1100	25.6	1700	143	
23956KW33C3	280	380	75	2.1	830	1750	710	1100	25.6	1700	143	
23956W33C3	280	380	75	2.1	830	1750	710	1100	26.4	1700	143	
23960	300	420	90	11,1	3	39,5	1200	2500	1300	1600	200	
23960K	300	420	90	3	1110	2320	650	1000	38.7	1600	200	