

RNA69 Series



select	Inquiry	Designation	Principal Dimensions(mm)				Cr	Cor	Fatigue load limit Cu	Reference speed	Limit speed	Weight
			Fw	D	C	r	(N)	(N)	(N)	U/min	U/min	(g)
RNA6918	105	125	63	1.1	195000	425000	74000	4250	2700	1330		
RNA6919	110	130	63	1.1	197000	440000	76000	4100	2450	1460		
RNA6917	100	120	63	1.1	188000	400000	71000	4450	2700	1200		
RNA6916	90	110	54	1.1	153000	300000	53000	4900	2850	987		
RNA6915	85	105	54	1	147000	275000	49500	5200	3050	935		
RNA6914	80	100	54	1	145000	265000	47500	5400	3250	857		
RNA6913	75	90	45	1	108000	198000	33500	600	3400	580		
RNA6912	68	85	45	1	106000	191000	32500	6400	3600	488		
RNA6911	63	80	45	1	102000	176000	30000	6900	3900	470		
RNA6909	52	68	40	0.6	79000	127000	21400	8200	4600	338		
RNA6908	48	62	40	0.6	74000	116000	19400	8900	5100	256		
RNA6907	42	55	36	0.6	54000	86000	15900	10100	5700	193		
RNA69/32	40	52	36	0.6	53000	82000	15100	10700	6000	162		
RNA6906	35	47	30	0.3	49000	71000	12900	12000	6100	126		
RNA69/28	32	45	30	0.3	63000	11400	12700	6700	135	135		
RNA6905	30	42	30	0.3	44000	59000	10600	13600	7200	112		
RNA6904	25	37	30	0.3	40500	51000	91000	15800	8500	100		
RNA6903	22	30	23	0.3	21100	29000	5100	18800	9500	42.4		
RNA6902	20	28	23	0.3	19500	25500	4450	20400	10600	39.7		
RNA6901	16	24	22	0.3	18100	21600	3800	23200	15900	31		
RNA 69-22	28	39	30	0.3	42000	55000	9900	14600	7800	98		
RNA6910	58	72	40	0.6	82000	139000	23400	7500	4150	310		