

NA49 Series

select	Inquiry	Designation	Principal Dimensions						Cr	Cor	Fatigue Load Cu	Limiting Speed nG	Reference Speed nB	Weight
			d	D	B	F	r	s						
NA4900	10 mm	22 mm	13 mm	14 mm	0,3 mm	0,5 mm	9600 N	9200 N	1630 N	25000 U/min	17300 U/min	23 g		
NA4901	12 mm	24 mm	13 mm	16 mm	0,3 mm	0,5 mm	10600 N	10900 N	1940 N	23600 U/min	14900 U/min	26 g		
NA4902	15 mm	28 mm	13 mm	20 mm	0,3 mm	0,5 mm	12000 N	13600 N	2430 N	21600 U/min	12000 U/min	34 g		
NA4903	17 mm	30 mm	13 mm	22 mm	0,3 mm	0,5 mm	12400 N	14600 N	2600 N	20600 U/min	10900 U/min	37 g		
NA4904	20 mm	37 mm	17 mm	25 mm	0,3 mm	0,8 mm	23700 N	25500 N	4600 N	17200 U/min	9600 U/min	75,2 g		
NA49/22	22	28	39	17	12996	19175	14360	76						
NA4905	25 mm	42 mm	17 mm	30 mm	0,3 mm	0,8 mm	26500 N	31500 N	5700 N	14600 U/min	7900 U/min	g		
NA49/28	28	32	45	17	13900	20100	13832	90.7						
NA49/32	32	40	52	20	19000	32600	11134	150						
NA4907	35 mm	55 mm	20 mm	42 mm	0,6 mm	0,8 mm	35500 N	50000 N	9400 N	10900 U/min	5000 U/min	170 g		
NA4908	40 mm	62 mm	22 mm	48 mm	0,6 mm	1 mm	48500 N	67000 N	11500 N	9600 U/min	5300 U/min	230 g		
NA4909	45 mm	68 mm	22 mm	52 mm	0,6 mm	1 mm	51000 N	73000 N	12600 N	8700 U/min	4750 U/min	271 g		
NA4910	50 mm	72 mm	22 mm	58 mm	0,6 mm	1 mm	53000 N	80000 N	13800 N	8000 U/min	4350 U/min	274 g		
NA4911	55 mm	80 mm	25 mm	63 mm	1 mm	1,5 mm	65000 N	100000 N	17300 N	7300 U/min	4100 U/min	393 g		
NA4912	60 mm	85 mm	25 mm	68 mm	1 mm	1,5 mm	68000 N	108000 N	18800 N	6800 U/min	3750 U/min	426 g		
NA4913	65 mm	90 mm	25 mm	72 mm	1 mm	1,5 mm	69000 N	112000 N	19500 N	6300 U/min	3500 U/min	456 g		
NA4914	70 mm	100 mm	30 mm	80 mm	1 mm	1,5 mm	95000 N	156000 N	27500 N	5800 U/min	3350 U/min	728 g		
NA4915	75 mm	105 mm	30 mm	85 mm	1 mm	1,5 mm	97000 N	162000 N	28500 N	5400 U/min	3150 U/min	775 g		
NA4916	80 mm	110 mm	30 mm	90 mm	1 mm	1,5 mm	101000 N	174000 N	30500 N	5200 U/min	2950 U/min	878 g		
NA4917	85 mm	120 mm	35 mm	100 mm	1,1 mm	1 mm	125000 N	237000 N	41500 N	4800 U/min	2800 U/min	1250 g		
NA4918	90 mm	125 mm	35 mm	105 mm	1,1 mm	1 mm	129000 N	250000 N	43500 N	4550 U/min	2650 U/min	1312 g		
NA4919	95 mm	130 mm	35 mm	110 mm	1,1 mm	1 mm	131000 N	260000 N	44500 N	4350 U/min	2550 U/min	1371 g		
NA4920	100 mm	140 mm	40 mm	115 mm	1,1 mm	2 mm	144000 N	270000 N	45500 N	4100 U/min	2600 U/min	1900 g		
NA4922	110 mm	150 mm	40 mm	125 mm	1,1 mm	2 mm	149000 N	290000 N	47500 N	3750 U/min	2400 U/min	2070 g		
NA4924	120 mm	165 mm	45 mm	135 mm	1,1 mm	2 mm	205000 N	390000 N	64000 N	3450 U/min	2200 U/min	2860 g		
NA4926	130 mm	180 mm	50 mm	150 mm	1,5 mm	1,5 mm	229000 N	470000 N	74000 N	3150 U/min	2080 U/min	3900 g		
NA4928	140 mm	190 mm	50 mm	160 mm	1,4 mm	1,5 mm	237000 N	500000 N	78000 N	2950 U/min	1920 U/min	4150 g		