

Shaft diameter from 180 mm to 340 mm

select	Inquiry Designation	Dimensions mm					Basic Load Rating kN		Fatigue Limit Load kN	Rated Speed r/min	Weight kg
		d	D	B	Cr	Cor				Reference Speed	Limiting Speed
61836	180	225	22	62,4	81,5	2,45	5600		3400	2,00	
61936MA	180	250	33	119	134	3,9	5300		4300	5,05	
16036	180	280	31	138	146	4,15	4800		4000	6,60	
6036M	180	280	46	190	200	5,6	4800		4000	10,5	
6236M	180	320	52	229	240	6,4	4000		3600	18,5	
6336M	180	380	75	351	405	10,4	3600		3200	42,5	
61838	190	240	24	76,1	98	2,8	5300		3200	2,60	
61938MA	190	260	33	117	134	3,8	5000		4300	5,25	
16038	190	290	31	148	166	4,55	4800		3000	7,90	
6038M	190	290	46	195	216	5,85	4800		3800	11,0	
6238M	190	340	55	255	280	7,35	3800		3400	23,0	
6338M	190	400	78	371	430	10,8	3400		3000	49,0	
61840	200	250	24	76,1	102	2,9	5000		3200	2,70	
61940MA	200	280	38	148	166	4,55	4800		3800	7,40	
16040	200	310	34	168	190	5,1	4300		2800	8,85	
6040M	200	310	51	216	245	6,4	4300		3600	14,0	
6240M	200	360	58	270	310	7,8	3600		3200	28,0	
61844	220	270	24	78	110	3	4500		2800	3,00	
61944MA	220	300	38	151	180	4,75	4300		3600	8,00	
16044	220	340	37	174	204	5,2	4000		2400	11,5	
6044M	220	340	56	247	290	7,35	4000		3200	18,5	
6244M	220	400	65	296	365	8,8	3200		3000	37,0	
6344M	220	460	88	410	520	12	3000		2600	72,5	
61848	240	300	28	108	150	3,8	4000		2600	4,50	
61948MA	240	320	38	159	200	5,1	4000		3200	8,60	

Shaft diameter from 180 mm to 340 mm

16048MA	240	360	37	178	220	5,3	3600	3000	14,5
6048M	240	360	56	255	315	7,8	3600	3000	19,5
6248M	240	440	72	358	465	10,8	3000	2600	51,0
6348M	240	500	95	442	585	12,9	2600	2400	92,5
61852	260	320	28	111	163	4	3800	2400	4,80